

NLII-CO2-R-5 | Combined sensor CO₂/RH

Combined sensor NLII-CO₂/RH is used to monitor air quality inside buildings and power control ventilation (HVAC) systems according to current levels of air internal air quality. The sensor measures concentration of carbon dioxide (CO₂) and relative humidity (RH) in air. It can be effectively used in offices, classrooms, shopping centers, homes, restaurants, fitness centers, commercial buildings, etc.



- > measures CO₂ and RH
- > 2x analog voltage/current output
- > 2x output relay – 2x NO/C
- > cascade switching
- > not required maintenance during operation
- > long life and stability

| Type of sensor | CO ₂ output | RH output | Relay |
|-------------------|--------------------------------------|--------------------------------------|----------------------|
| NLII- CO2 –R-5 | 0-10 V/0-20 mA/4-20 mA ¹⁾ | - | 1x switching contact |
| NLII- CO2 +RH-R-5 | 0-10 V/0-20 mA/4-20 mA ¹⁾ | 0-10 V/0-20 mA/4-20 mA ¹⁾ | 2x NO/C |

¹⁾ It is possible to select by jumper desired type of analog output. Minimum achievable output value corresponds to minimum value of the measuring range.

The measuring of CO₂ is based on the principle of infrared radiation attenuation dependence on the CO₂ concentration in the air (NDIR). Built-in auto-calibration function ensures very good long term stability.

Measurement of the relative humidity is based on the principle of capacitive polymer sensor. The sensor has built-in two separate analog outputs - one for the actual concentration of CO₂ and the other for the current relative humidity. If the sensor contains 2 relays can be set two switching modes: standard (always one relay switched according to one quantity), a cascade mode (according to a selected quantity switch two relays with different levels of switching). Cascade switching, for example, can be used to switch power air conditioning units. The two rotary switches can be independently set the level at which the corresponding relay switches.

Sensor can efficiently manage ventilation and heat recovery units, based on current air quality.

By three LED indicators can be easily checked the current air quality. Preferred eco level means good indoor air quality needed to achieve a sense of well-being and at the same time can reduce energy costs for heating or air conditioning. Based on these measurements can be directly controlled ventilation, air conditioning and heat recovery units in an efficient manner.



NLII-CO2-R-5 | Combined sensor CO₂/RH

| Parameter | Value | Unit |
|------------------------------------|----------------------------|-------------|
| Supply voltage range | 14 – 40 | V DC |
| | 18 – 30 | V AC |
| Average consumption | 0,5 | W |
| CO ₂ measuring range | 400 – 5000 | ppm |
| CO ₂ accuracy | ± 35 ppm + ±5 % of reading | |
| CO ₂ relay - hysteresis | 100 | ppm |
| CO ₂ rate rise | max 1 | min |
| CO ₂ step response | (90 %) 80 | s |
| RH measuring range | 0 – 100 % | RH |
| RH accuracy 20 – 80 % | ± 3 % | RH |
| RH accuracy 0 – 100 % | ± 6 % | RH |
| RH switching hysteresis | 5 % | RH |
| Max. switching voltage | 250/30 | V AC / V DC |
| Max. switching current | 5/5 | A AC / A DC |
| Working humidity non condensing | 0 – 95 % | RH |
| Working temperature | 0 to +50 | °C |
| Storage temperature | -20 to +60 | °C |
| Expected lifetime | min. 10 | years |
| Ingress protection | IP20 | |
| Dimensions | 90x80x31 | mm |

